

AMENDMENTS TO THE CLAIMS

1. (AMENDED) A modular thermal reformer system assembly, comprising:
a top end plate;
a bottom end plate; and,
a plurality of planar modular assembly including a reformer elements zone stacked together between the top end plate and the bottom end plate; wherein each modular element comprises:
a ~~combustion zone, an inlet reformat~~ inlet component layer;
a ~~process fluid manifold, an outlet reformat~~ outlet component layer;
a ~~process fluid manifold, an inlet combustion~~ inlet component layer;
a ~~fluid manifold, an combustion~~ outlet component layer; and a reformation cavity and combustion cavity centrally located within the modular reformer element;
~~outlet combustion fluid manifold, an inlet reformat process fluid flow passage connecting the inlet reformat process fluid manifold and the reformer zone, an outlet reformat process fluid flow passage connecting the reformer zone and the outlet reformat process fluid manifold, an inlet combustion fluid flow passage connecting the inlet combustion fluid manifold and the combustion zone, and an outlet combustion fluid flow passage connecting the combustion zone and the outlet combustion fluid manifold.~~
wherein the reformat inlet component layer comprises an inlet reformat manifold located at an outer edge of the reformat inlet component layer , an inlet reformat process fluid flow passage , and an inlet flow distribution region , wherein the inlet reformat manifold allows for entry of a reformat process fluid into the inlet reformat process fluid flow passage for the inward flow of reformat process fluid towards the inlet flow distribution region and into the centrally located reformation cavity; and,
wherein the reformat outlet component layer comprises a reformat outlet manifold located at an outer edge of the reformat outlet component layer , an outlet reformat process fluid flow passage and an outlet distribution region , wherein the outlet reformat process fluid flow passage allows for the outward flow of reformat process fluid from the centrally located

reformation cavity and the outlet distribution region and the reformat outlet manifold allows for the exit of reformat process fluid from the outlet reformat process fluid flow passage.

2. (AMENDED) The assembly ~~thermal reformer system~~ of claim 17, wherein said the inlet reformat ~~[[er]] inlet component layer zone~~ and combustion inlet component layer zone are be in thermal contact to promote transfer of combustion heat into said the reformat inlet component layer ~~reformer zone to drive a reaction in said reformer zone.~~

3. (CANCELED)

4. (CANCELED)

5. (CANCELED)

6. (AMENDED) The assembly ~~thermal reformer system~~ of claim 17, wherein said inlet combustion reformat process fluid flow passage is in thermal contact with said outlet combustion reformat process flow passage and/or said outlet ~~combustion fluid flow passage to promote transfer of heat from outlet fluid(s) to inlet fluid(s).~~

7. (AMENDED) The assembly ~~thermal reformer system~~ of claim 1, wherein said inlet reformat process fluid flow passage is located circumferentially within the assembly extending counter-clockwise from the inlet reformat manifold located at an outer edge of the reformat inlet component layer towards the inlet flow distribution region and into the centrally located reformation cavity, and wherein the outlet reformat process fluid flow passage extends clockwise from the centrally located reformation cavity and the outlet distribution region towards the reformat outlet manifold located at an outer edge of the reformat outlet component layer.

8. (CANCELED)

9. (CANCELED)

10. (CANCELED)

11. (CANCELED)

12. (CANCELED)

13. (CANCELED)

14. (CANCELED)

15. (CANCELED)

16. (AMENDED) The modular thermal reformer ~~system~~ assembly of claim 1, wherein ~~one or more of said inlet~~ the reformat outlet process fluid manifold is in fluid connection with, ~~an outlet reformat process fluid a manifold of the reformat inlet component layer~~ an inlet combustion fluid manifold, an outlet combustion fluid manifold is external to said planar assembly.

17. (AMENDED) The modular thermal reformer assembly ~~system~~ of claim 1, wherein ~~said the assembly is constructed of sheet metal components.~~ the combustion inlet component layer comprises a combustion inlet manifold located at an outer edge of the combustion inlet component layer, an inlet combustion process fluid flow passage and a combustion fluid flow distribution region, wherein the a combustion inlet manifold allows for entry of a combustion process fluid into the inlet combustion process fluid flow passage for the inward flow of combustion process fluid towards the combustion fluid flow distribution region and into the centrally located combustion cavity; and,

combustion outlet component layer comprises a combustion outlet manifold located at an outer edge of the combustion outlet component layer, an outlet combustion process fluid flow passage and an outlet distribution region, wherein the outlet combustion process fluid flow passage allows for the outward flow of combustion process fluid from the centrally located

combustion cavity and the outlet distribution region and the combustion outlet manifold allows for exit of the combustion process fluid from the outlet combustion process fluid flow passage.

18. (CANCELED)

19. (NEW) The modular thermal reformer assembly of claim 1, wherein inlet combustion process fluids flow to the combustion inlet manifold through a manifold port of the reformat inlet component layer and a manifold port of the reformat outlet component layer; and,

wherein the combustion outlet manifold is in fluid connection with a manifold of the combustion inlet component layer, a manifold port of the reformat outlet component layer, and a manifold port of the reformat inlet component layer.

20. (NEW) The modular thermal reformer assembly of claim 1, wherein inlet reformat process fluids flow through a manifold port of the combustion inlet component layer and a manifold port of the combustion outlet component layer, and wherein outlet reformat process fluids flow through a manifold port of the combustion inlet component layer and a manifold port of the combustion outlet component layer; and,

wherein the reformation cavity is in thermal contact with the combustion cavity.

21. (NEW) The assembly of claim 17 wherein the inlet combustion process fluid flow passage extends counter-clockwise from the combustion inlet manifold located at an outer edge of the combustion inlet component layer towards the combustion fluid flow distribution region and into the centrally located combustion cavity, and wherein the outlet combustion process fluid flow passage extends clockwise from the centrally located combustion cavity and the outlet distribution region towards the combustion outlet manifold located at an outer edge of the combustion outlet component layer.